

# Super Steel Saver

2.2 VOC Direct Over Rust Corrosion Resistant Coating



ZOLATONE®

## Features:

- Easy Application
- High Gloss
- Seals Rust

## Advantages:

- Superior Corrosion Resistance
- Better UV Protection
- Lower Material Costs

## Benefits:

- Increased Productivity
- Increased Profitability
- Improved Finish

## Compare To:

POR 15 Inc.  
Magnet Paints  
KBS Coatings

POR 15  
Chassis Saver  
Rust Seal

**Professional Grade Products**

# Super Steel Saver

2.2 VOC Direct Over Rust Corrosion Resistant Coating

## About ZT-SS Series

ZT-SS Series is a 2.25 VOC Moisture Cure Urethane Rust Sealer is a high solids product designed to be painted directly over rust or weathered metal surfaces to seal in the rust and keep it from spreading. The non-porous nature of this high performance engineered polymer makes it impervious to water, chemicals, salt and other corrosive substances.

## Tech Specs

Color:	Gloss Black, Silver Aluminum
Mix Ratio:	Ready to Spray
Weight Solids(RTS):	75%
Film Build:	2-3 dry mils per coat
Coverage:	350 sq ft./gal
Dry Time:	2-4 Hours
Pot Life:	N/A*
V.O.C.	2.25 lbs/gal

## Instructions

Super Steel Saver products require a surface profile to penetrate into. Slick or new metal surfaces must be sanded with 60 - 80 grit sandpaper. If sand blasting, provide a medium to coarse profile for proper adhesion.

**Mixing Instructions:** Do Not Shake! Open the container carefully in case of pressure build up. Stir with stick. If entire contents of container is not going to be used; then using small cups, dip out the amount of product needed and pour it into a separate container.

**General Application:** The surface must be free from dirt, oil, grease and other contaminates. Surface must be completely dry, free of any moisture. Apply a minimum of 2 coats to achieve the maximum protection. Allow at least 3 hours between coats. Each coat should be dry to touch before applying the next coat. Applying heavy coats may cause bubbling. Avoid bubbling by applying multiple thin coats.



**Professional Grade Products**